

# STABILIZÁTORY

## Stabilizátory kladného napětí do 100mA

obj. název	U out	±Uout	Iout	Uin	prac. teplota	pouzdro
	V	%	A	V	°C	
■ LM2936Z - 5.0	5.0	3	0.05		-40 ... +125	TO 92
■ 78L05	5.0	5	0.1	7.0 ... 20	0 ... +125	TO 92
■ 78L06A CZ	6.0	5	0.1	8.5 ... 20	0 ... +125	TO 92
■ 78L08A CZ	8.0	5	0.1	10.5 ... 22	0 ... +125	TO 92
■ 78L09	9.0	5	0.1	11.5 ... 23	0 ... +125	TO 92
■ 78L10	10.0	10	0.1	13.0 ... 25	0 ... +125	TO 92
■ 78L12	12.0	5	0.1	14.5 ... 27	0 ... +125	TO 92
■ 78L15	15.0	5	0.1	17.5 ... 30	0 ... +125	TO 92
■ LP2951A CM -3.3	3.3	2	0.1		-40 ... +125	SO 8
■ LD2979 M50TR	5.0	2	0.05		-25 ... +125	SOT23-5
■ 78L05F SMD	5.0	5	0.15	7.0 ... 20	-30 ... +75	SOT 89
■ 78L05S SMD	5.0	5	0.1	7.0 ... 20	0 ... +125	SO 8
■ 78L09A CD SMD	9.0	5	0.1	11.5 ... 23	0 ... +125	SO 8
■ 78L12S SMD	10.0	5	0.1	14.5 ... 27	0 ... +125	SO 8
■ 78L15A CD SMD	15.0	5	0.1	17.5 ... 30	0 ... +125	SO 8

## Stabilizátory záporného napětí, 100mA

obj. název	U out	±Uout	Iout	Uin	prac. teplota	pouzdro
	V	%	A	V	°C	
■ 79L05	-5.0	5	0.1	-7 ... -20	0 ... +125	TO 92
■ 79L09 CT	-9.0	5	0.1	-11.5 ... -23	0 ... +125	TO 92
■ 79L12	-12.0	5	0.1	-14.5 ... -27	0 ... +125	TO 92
■ 79L15A CZ	-15.0	5	0.1	-17.5 ... -30	0 ... +125	TO 92
■ 79L05S SMD	-5.0	5	0.1	-7 ... -20	0 ... +125	SO 8
■ 79L09A CD SMD	-9.0	5	0.1	-11.5 ... -23	0 ... +125	SO 8
■ 79L12A CD SMD	-12.0	5	0.1	-14.5 ... -27	0 ... +125	SO 8

## Stabilizátory kladného napětí, 500mA

obj. název	U out	±Uout	Iout	Uin	prac. teplota	pouzdro
	V	%	A	V	°C	
■ 78M20 CV	20	4	0.5		0 ... +125	TO 220
■ 78M05 CDT SMD	5.0	10	0.5		0 ... +125	DPAK
■ 78M10 CDT SMD	10.0	10	0.5		0 ... +125	DPAK

## Stabilizátory záporného napětí, 1A

obj. název	U out	±Uout	Iout	Uin	prac. teplota	pouzdro
	V	%	A	V	°C	
■ 7905 CV	-5.0	5	1	-7 ... -20	0 ... +125	TO 220
■ 7908 CV	-8.0	5	1	-10.5 ... -23	0 ... +125	TO 220
■ 7909 CV	-9.0	5	1	-11.5 ... -24	0 ... +125	TO 220
■ 7912 CV	-12.0	5	1	-14.5 ... -27	0 ... +125	TO 220
■ 7915 CV	-15.0	5	1	-17.5 ... -30	0 ... +125	TO 220
■ 7918 CV	-18.0	5	1	-22 ... -33	0 ... +125	TO 220
■ 7924 CV	-24.0	5	1	-28 ... -38	0 ... +125	TO 220

## Stabilizátory kladného napětí, 1A

obj. název	U out	±Uout	Iout	Uin	prac. teplota	pouzdro
	V	%	A	V	°C	
■ MIC 2940A -5.0BT	5.0	2	1.25		-40 ... +125	TO 220
■ 7805 CV	5.0	5	1	8.0 ... 20	0 ... +125	TO 220
■ 7806 CV	6.0	5	1	9.0 ... 21	0 ... +125	TO 220
■ 7808 CV	8.0	5	1	10.5 ... 23	0 ... +125	TO 220
■ 7809 CV	9.0	5	1	11.5 ... 24	0 ... +125	TO 220
■ 7812 CV	12.0	5	1	14.5 ... 27	0 ... +125	TO 220
■ 7815 CV	15.0	5	1	17.5 ... 30	0 ... +125	TO 220
■ 7818 CV	18.0	5	1	22 ... 33	0 ... +125	TO 220
■ 7824 CV	24.0	5	1	28 ... 38	0 ... +125	TO 220
■ 7805C D2T SMD	5.0	5	1	8.0 ... 20	0 ... +125	D2PAK

## Stabilizátory záporného napětí nastavitelné

obj. název	U out	±Uout	Iout	Uin	prac. teplota	pouzdro
	V	%	A	V	°C	
■ LM 337 T	-1.2 ... -37	1	1	-3 ... -40	0 ... +125	TO 220

## Stabilizátory kladného napětí, 2A

obj. název	U out	±Uout	Iout	Uin	prac. teplota	pouzdro
	V	%	A	V	°C	
■ 78S05 CV	5.0	5	2	7.0 ... 25	0 ... +125	TO 220
■ 78S09 CV	9.0	5	2	11 ... 25	0 ... +125	TO 220
■ 78S12 CV	12.0	5	2	14.5 ... 30	0 ... +125	TO 220
■ 78S15 CV	15.0	5	2	17.5 ... 30	0 ... +125	TO 220
■ 78S18 CV	18.0	5	2	20.5 ... 30	0 ... +125	TO 220
■ 78S24 CV	24.0	5	2	27 ... 38	0 ... +125	TO 220

## Referenční zdroje

obj. název	U out	±Uout	Tc	Uin	prac. teplota	pouzdro
	V	%	ppm/K	V	°C	
■ LT 1004C LP-1,2	1.235		20	1.5 ... 9	0 ... +70	TO 92
■ LM 385 Z -1,2	1.235	2	80	2.3 ... 30	0 ... +70	TO 92
■ LM 236 Z	2.50	2			-25 ... +85	TO 92
■ LM 285 Z -2,5	2.50	1.5	80	3.7 ... 30	-40 ... +85	TO 92
■ LM 385 Z -2,5	2.50	3	80	3.7 ... 30	0 ... +70	TO 92
■ LM 385B Z -2,5	2.50	1.5	80	3.7 ... 30	0 ... +70	TO 92
■ AD 680 AR	2.50			4.5 ... 36	-40 ... +85	SO 8

## Stabilizátory kladného napětí nízkoubytkové

obj. název	U out	±Uout	Iout	Uin	prac. teplota	pouzdro
	V	%	A	V	°C	
■ LT1129 IQ -3.3	3.3	3	0.7		-40 ... +125	TO 263-5
■ LE 33 CZ	3.3	2	0.1	4 ... 18	-40 ... +125	TO 92
■ LE 50 CZ	5.0	2	0.1	5.7 ... 18	-40 ... +125	TO 92
■ LM 2940CT-5	5.0	3	1	6.25 ... 26	0 ... +125	TO 220
■ L 4940 V 5	5.0	4	1.5	6.5 ... 16	-40 ... +125	TO 220
■ MAX 667 CPA	5.0	4	0.25	5.5 ... 16	0 ... +70	DIP 8
■ LT1129CST-3.3SMD	3.3	3	0.7	4.3 ... 30	0 ... +125	SOT 223
■ LE 33 CD SMD	3.3	2	0.1	4 ... 18	-40 ... +125	SO 8
■ LE 50 CD SMD	5.0	2	0.1	5.7 ... 18	-40 ... +125	SO 8

## Stabilizátory kladného napětí nastavitelné

obj. název	U out	±Uout	Iout	Uin	prac. teplota	pouzdro
	V	%	A	V	°C	
■ LM 317LZ	1.2 ... 37	1	0.1	3 ... 40	0 ... +125	TO 92
■ TL 431I LP	2.5 ... 36		0.1	3 ... 37	-40 ... +85	TO 92
■ TL 431 CT	2.5 ... 36		0.1	3 ... 37	0 ... +70	TO 92
■ TL 431B CT	2.5 ... 36		0.1	3 ... 37	0 ... +70	TO 92
■ UA 723 CN	2 ... 37	5	0.15	5 ... 40	0 ... +70	DIP 14
■ LM 723 CN	2 ... 37	5	0.15	5 ... 40	0 ... +70	DIP 14
■ LM 317 T	1.2 ... 37	1.5	1.5	2.5 ... 40	0 ... +125	TO 220
■ LM 317A T	1.2 ... 37	1	1.5	2.5 ... 40	0 ... +125	TO 220
■ L200 CV	2.8 ... 36	1	2	4 ... 40	-25 ... +125	TO 220-5
■ LM 317LD SMD	1.2 ... 37	1	0.1	3 ... 40	0 ... +125	SO 8
■ LP2951A CS	1.2 ... 29		0.1	3 ... 32	0 ... +125	SO 8
■ TL 431A I D SMD	2.5 ... 36		0.1	3 ... 37	-40 ... +85	SO 8
■ TL 431A CD SMD	2.5 ... 36		0.1	3 ... 37	0 ... +70	SO 8