





ELEKTROAKUSTICKÉ MĚNIČE



HC

Elektromagnetické měniče s cizím buzením



objednací název	obj.č.	Un (U/Umax) V	In mA	odpor cívky Ω	výkon dB	kmitočet Hz	hmotnost g	RM mm	prac. teplota °C
■ HCS 0903F	50745	3 (2 / 5)	80	16 ± 2	85	2730	0.6	SMD	-40 / +85
■ HCS 0903G	50746	3 (2 / 5)	80	18 ± 3	85	2730	0.5	SMD	-40 / +85
■ HC 12G-1P	50747	1.5 (1 / 5)	30	16 ± 2	85	2048	2.0	6.5	-25 / +70
■ HC 12G-2P	50748	1.5 (1 / 5)	15	42 ± 6	80	2048	2.0	6.5	-25 / +70
■ HCM 1206A	50749	6 (4 / 8)	60	45 ± 5	85	2400	2.0	6.5	-40 / +85
■ HCM 1212A	50750	12 (7 / 16)	60	140 ± 14	85	2400	2.0	6.5	-40 / +85





HCS 0903F



HCS 0903G



HC 12G





HCM 12



HC_X

Elektromagnetické měniče s vestavěným oscilátorem

objednací název	obj.č.	Un (U/Umax) V	In mA	odpor cívky Ω	výkon dB	kmitočet Hz	hmotnost g	RM mm	prac. teplota °C
■ HCM 1206X	50753	6 (3 / 7)	30	--	85	2300	2.0	7.6	-40 / +85
■ HCM 1212X	50754	12 (8 / 15)	30	--	85	2300	2.0	7.6	-40 / +85
■ HCM 1206BX	50756	6 (3 / 7)	30	--	83	2300	1.6	7.6	-20 / +80
■ HCM 1212BX	50755	12 (8 / 16)	30	--	83	2300	1.6	7.6	-20 / +80



HCM 12_X



HCM 12_BX

